

SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Identifier : **ARDEX P 82™ ULTRA PRIME Hardener (Part B)**
Product Code Number : 70011791
Chemical Family : Mixture, Water-based epoxy hardener
Trade Name/Synonyms : ARDEX P 82 Hardener
Material Use : For the installation of ARDEX underlayments over non-porous, wood and metal substrates and adhesive residue on concrete.
Uses Advised Against : Use only as recommended in the product's Technical Data Sheet.
Manufacturer's name and address:



ARDEX L.P.
400 Ardex Park Dr.
Aliquippa, PA 15001 USA

Information Telephone No. : (888) 512-7339 or (724) 203-5000
Website Address : <http://www.ardexamericas.com>
24 Hr Emergency Telephone # : CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)

SECTION 2 – HAZARDS IDENTIFICATION

GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

: Skin Sensitization 1
Eye Irritation 2A
Skin Irritation 2
Specific Target Organ Toxicity, Single Exposure, Category 3, Respiratory

GHS Pictograms :



Signal Word : Warning

Hazard Statements : Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.

Precautionary Statements : Avoid breathing vapor. Do not get in eyes, on skin or on clothing. Wear protective gloves/protective clothing/eye protection. Use only in a well-ventilated area. Wash hands and exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Clean contaminated clothing before reuse. Store in a well-ventilated place. Store in a closed container. Store locked up. Dispose of contents / container in accordance with federal, state, and local laws. Do not allow product to enter drains.

Hazards not otherwise classified : None.

% With Unknown Acute Toxicity : Up to 15% by weight of this product is comprised of ingredients with unknown acute toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
Benzyl alcohol	100-51-6	1.00 – 5.00
Isophoronediamine	2855-13-2	1.00 – 5.00
Triethylenetetramine	112-24-3	1.00 – 5.00

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

SECTION 4 – FIRST AID MEASURES

- General** : Call a Poison Center or doctor if you feel unwell.
- Inhalation** : Remove person to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: call a doctor/physician.
- Skin contact** : Remove/Take off immediately all contaminated clothing. Flush affected skin with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention.
- Eye contact** : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- Ingestion** : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.
- Notes for Physician** : Treat symptomatically.
- Signs and symptoms of short-term (acute) exposure**
- Inhalation* : May cause irritation to the respiratory system producing mild coughing.
 - Skin* : May cause redness, itching, and swelling. Contains components which are easily absorbed through the skin.
 - Eyes* : Symptoms may include redness, tears in the eyes, itching, blurred vision, or pain.
 - Ingestion* : May cause gastric pain, nausea, vomiting, or diarrhea.
- Effects of long-term (chronic) exposure**
- : Some individuals may experience a sensitization reaction of the skin after an initial exposure. Subsequent exposures may cause a hypersensitive skin reaction (rash, swelling).
- Indication of need for immediate medical attention or special treatment**
- : Difficulty breathing persists after removing the person to fresh air.
 - : Any exposure to the eye which causes irritation.
 - : Blue color of the skin (cyanotic) after exposure, or chemical burns to the skin.
 - : Ingestion.

SECTION 5 – FIRE FIGHTING MEASURES

- Suitable extinguishing media** : Carbon dioxide, dry chemical, alcohol-resistant foam, or water spray.
- Unsuitable extinguishing media** : water jet; may cause fire to spread.
- Hazardous combustion products** : Carbon monoxide, carbon dioxide, nitrogen oxides, ammonia, and other vapors and gases that are common to the thermal degradation of organic compounds.
- Special fire-fighting procedures/equipment**
- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.
- Fire hazards/conditions of flammability**
- : Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.
- Flammability classification (OSHA 29 CFR 1910.1200 and WHMIS 2015)**
- : Nonflammable
- Environmental precautions** : Do not allow product to enter waterways. Do not allow material to contaminate ground water system.
- NFPA Rating** Hazard Rating Scale: 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe
Health: 2 Flammability 1 Reactivity 0 Special Hazards 0

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- Personal precautions** : See Section 7 for safe handling procedures. Wear chemically resistant personal protective equipment during cleanup. Restrict access to area until completion of clean-up. All persons dealing with clean-up must be properly trained and wear the appropriate chemically protective equipment.
- Protective equipment** : Refer to Section 8 for information on acceptable personal protective equipment.
- Emergency procedures** : This product does not contain any chemicals which require reporting spills or releases to the U.S. EPA. In case of a spill or release, call the emergency number listed in Section 1 for advice.
US CERCLA Reportable quantity (RQ): None reported.
- Spill response / clean-up** : Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal. While the material is still wet, use warm water to clean up residue. Notify the appropriate authorities as required.
- Prohibited materials** : None known.
- Environmental precautions** : Do not allow product to enter waterways. Do not allow material to contaminate ground water system.
- Disposal** : See Section 13 for disposal information.

SECTION 7 – HANDLING AND STORAGE

- Safe handling procedures** : Avoid contact with eyes, skin or clothing. Avoid breathing vapors. Do not swallow. Observe good hygiene standards. Use only with adequate ventilation. Do not eat, drink or smoke in the work area. Wash thoroughly after handling. Avoid repeated or prolonged contact with the skin. People with a history of skin sensitization or asthma, allergies, chronic or recurring respiratory illnesses should not be involved in any process in which this preparation is used. Once a person is sensitized, no further exposure to the sensitizing material should be allowed. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Avoid storing in direct sunlight. Store in original container. Keep tightly closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.
- Incompatible materials** : See Section 10.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Permissible Exposure Limits** : No exposure limits have been established for the product. Below are exposure limits for the components in the product.

Ingredients	CAS #	ACGIH TLV		OSHA PEL	
		TLV	STEL	PEL	STEL
Benzyl alcohol	100-51-6	10 ppm WEEL	N/Av	10 ppm AIHA	N/Av
Isophoronediamine	2855-13-2	N/Av	N/Av	N/Av	N/Av
Triethylenetetramine	112-24-3	1 ppm (skin)	N/Av	N/Av	N/Av

- Engineering controls** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor or mist generated from the handling of this product.
- Personal Protection Equipment**
- Eye / face protection** : Safety glasses or chemical goggles must be worn when using this product. A face shield is recommended if splashing is possible.
- Skin protection** : Wear chemical resistant protective clothing and impervious gloves. Materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended. Contact the glove manufacturer for the breakthrough times for the ingredients listed in Section 3.

- Body protection** : Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.
- Respiratory protection** : If the work process generates excessive quantities of vapor or dust, or exposures in excess of any PEL, wear an appropriate organic vapor respirator approved by NIOSH.
- Site safety equipment** : An eyewash station and safety shower should be made available in the immediate working area.
- General hygiene considerations** : Avoid contact with eyes, skin and clothing. Do not breathe vapors/dust. Do not eat, drink or smoke when using this product. Clean all equipment and clothing at end of each work shift. Carefully wash hands and

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|---|----------------------------|--|----------------------------|
| Physical state | : Liquid | Appearance | : White |
| Odor | : Amine | Odor threshold | : N/Av |
| pH | : < 11.50 | Specific gravity | : 1.20 |
| Boiling point | : 212°F (100°C) | Coefficient of water/oil distribution | : N/Av |
| Melting/Freezing point | : N/Av | Solubility in water | : Miscible |
| Vapor pressure (mm Hg @ 20°C / 68°F) | : N/Av | Evaporation rate (<i>n</i>-Butyl acetate = 1) | : N/Av |
| Vapor density (Air = 1) | : N/Av | Volatiles (% by weight) | : 55 – 60 (includes water) |
| Volatile organic compounds (VOCs) | : 5.5 g/L, A+B, ASTM D2369 | | |
| Flammability classification | : Nonflammable | Decomposition temperature | : N/Av |
| Flash point | : >200°F (>93.3°C) | Lower flammable limit (% by vol) | : N/Av |
| Flash point method | : Setflash closed | Upper flammable limit (% by vol) | : N/Av |
| Auto-ignition temperature | : N/Av | Oxidizing properties | : None |
| Flame projection length | : N/Av | Flashback observed | : N/Av |
- Explosion data: Sensitivity to mechanical impact / static discharge**
: Not expected to be sensitive to mechanical impact or static discharge.
- Viscosity** : N/Av

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

- Reactivity** : Reacts with epoxides or isocyanates.
- Stability** : Stable under the recommended storage and handling conditions prescribed.
- Hazardous polymerization** : Hazardous polymerization does not occur.
- Conditions to avoid** : Avoid prolonged exposure to heat.
- Materials to avoid and incompatibility**
: Strong oxidizing agents.
- Hazardous decomposition products**
: Refer to hazardous combustion products in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

- Routes of exposure** : *Inhalation*: YES *Skin Absorption*: YES *Skin and Eyes*: Yes *Ingestion*: YES
- Symptoms of exposure** : See Section 4.
- Calculated Acute Toxicity Estimates for the Product**
- | | |
|-------------------|------------------|
| <i>Inhalation</i> | : N/Av |
| <i>Oral</i> | : > 3000 mg/kg |
| <i>Dermal</i> | : > 10,000 mg/kg |
- Toxicological data** : Based on individual components, this product is an irritant to skin and eyes, and can cause sensitization by skin contact. See below for individual ingredient acute toxicity data.

Ingredients	CAS No.	LC50 (4 hr) Inhalation, rat	LD50 Oral, rat	LD50 Dermal, rabbit

Triethylenetetramine	112-24-3	N/Av	2500	805
Isophoronediamine	2855-13-2	> 5.01	1030	1840
Benzyl alcohol	100-51-6	8.8	1230	2000

- Skin corrosion or irritation** : Causes irritation to skin.
- Serious eye damage / eye irritation** : Causes severe irritation to eyes.
- Respiratory or skin sensitization** : Contains amines, which are known to cause skin sensitization reactions.
- Germ cell mutagenicity** : None known.
- Carcinogenic status** : No components are listed as carcinogens by ACGIH, IARC, OSHA, NIOSH or NTP.
- Reproductive toxicity** : None known.
- Specific Target Organ Toxicity, Single Exposure** : May cause respiratory irritation.
- Specific Target Organ Toxicity, Repeated Exposure** : None known.
- Aspiration hazard** : None known.
- Additional information** : N/Av

SECTION 12 – ECOLOGICAL INFORMATION

- Environmental effects** : The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.
- Ecotoxicological** : No data is available on the product itself. Information on components is listed below.
- Persistence and degradability** : Not Available.
- Bioaccumulative potential** : Not Available.
- Mobility in soil** : Not Available.
- PBT and VPVB assessments** : Not Available.
- Other Adverse Effects** : Material is alkaline and should not be discharged into sewers or waterways.

SECTION 13 – DISPOSAL CONSIDERATION

- Handling for disposal** : Handle waste according to recommendations in Section 7.
- Methods of disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
- Packaging** : Handle contaminated packaging in the same manner as the product.
- RCRA** : For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	Not regulated.	Not regulated.	None	None
TDG Additional Information	None				
49 CFR/DOT	None	Not regulated.	Not regulated.	None	None
49 CFR/DOT Additional Information	None				

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

- Skin Sensitization 1
- Eye Irritation 2A
- Skin Irritation 2
- Specific Target Organ Toxicity, Single Exposure, Category 3, Respiratory

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The threshold for this product is 10,000 pounds.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above *de minimus* concentrations.

U.S. State Right to Know Laws

California Proposition 65: See product label for information regarding Proposition 65.

Other State Right to Know Laws:

Component	CAS	CA	MA	MN	NJ	NY	PA	RI
Triethylenetetramine	112-24-3	No	Yes	No	Yes	No	Yes	No
Isophoronediamine	2855-13-2	No	No	Yes	Yes	No	No	No
Benzyl alcohol	100-51-6	No	Yes	No	No	No	Yes	No

SECTION 16 – OTHER INFORMATION

HMIS Rating : * - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe
 Health: *2 Flammability 1 Physical Hazard 0
 Recommended PPE: Gloves, safety glasses with side shields, protective clothing

Legend : ACGIH: American Conference of Governmental Industrial Hygienists
 CAS: Chemical Abstract Services
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
 CFR: Code of Federal Regulations
 DOT: Department of Transportation
 DSL: Domestic Substances List
 EPA: Environmental Protection Agency
 GHS: Globally Harmonized System
 HPR: Hazardous Products Regulations
 IARC: International Agency for Research on Cancer
 Inh: Inhalation
 N/Av: Not Available
 N/Ap: Not Applicable
 NIOSH: National Institute of Occupational Safety and Health
 NTP: National Toxicology Program
 OSHA: Occupational Safety and Health Administration
 PEL: Permissible exposure limit
 RCRA: Resource Conservation and Recovery Act
 SARA: Superfund Amendments and Reauthorization Act
 STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WEEL: Workplace Environmental Exposure Level
WHMIS: Workplace Hazardous Materials Identification System

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user determines the adequacy of the safety procedures employed during the use of this product. No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By:

ARDEX L.P.
400 Ardex Park Drive
Aliquippa, PA, U.S.A.
15001

(724) 203-5000
Visit our Website: <http://www.ardexamericas.com>

Revision date: : 05-Jan-2021

End of Document