



ARDEX AMERICAS | Non-Structural Patching Compounds

ARDEX		Exterior	Trowel	Pour	Concrete	Wood	Masonry	Terrazzo	Ceramic Tile	Quarry Tile	Adhesive Residues	True Feather-edge	Minimum	Maximum	Walk on	Install Floor Covering	Coverage / bag	CHOOSE...	RH Limit
ARDEX FEATHER FINISH®			●		●	●	●	●	●	●	●	●	Featheredge	1/2 inch 12.7 mm	15 minutes	15 to 20 minutes	300 sq. ft. at a skim coat 27.8 m ²	Unrivaled Performance	99% RH
ARDEX FEATHER FINISH® XF™			●		●	●	●	●	●	●	●	●	Featheredge	1/2 inch 12.7 mm	15 minutes	15 to 20 minutes	300 sq. ft. at a skim coat 27.8 m ²	High Performance	95% RH
ARDEX MRF™	interior	●	●		●	●	●	●	●	●	●	●	Featheredge	unlimited in well-defined areas	30 minutes	30 minutes	28 sq. ft. at 1/8"	Weatherproof	100% RH
	exterior	●	●		●	●	●	●	●	●	●	●	Featheredge	1/4" in well-defined areas	30 minutes	30 minutes	28 sq. ft. at 1/8"	Weatherproof	100% RH
ARDEX SD-P® RAPID			●		●			●	●	●			Featheredge	1 inch, 3 inches with aggregate 2.5 to 7.6 cm	15 minutes	60 minutes	50 sf at 1/8 inch 4.6 m ² at 3 mm	Ramping and Screeding with Faster Setting	99% RH
ARDEX SD-P®			●		●			●	●	●			Featheredge	1 inch, 3 inches with aggregate 2.5 to 7.6 cm	15 minutes	90 minutes	50 sf at 1/8 inch 4.6 m ² at 3 mm	Ramping and Screeding with Longer Open Time	99% RH
ARDEX FORTI FINISH™			●		●						●		Featheredge	1/2 inch 12.7 mm	15 to 30 minutes	15 to 30 minutes	40 sf at 1/16 inch 3.7 m ² at 1.5 mm	High Strength	99% RH
ARDEX SKM™ Skim Finish			●		●	●			●	●	●	●	Featheredge	1/2 inch 12.7 mm	30 minutes	1 to 2 hours	150-200 sf at a skim coat 14-18.5m ²	Skim Coat	95% RH
ARDEX GPS™			●		●	●		●	●	●	●		Featheredge	1/2 inch 12.7 mm	30 minutes	1 to 2 hours	65 sf at 1/8 inch 6 m ² at 3 mm	General Purpose	95% RH
ARDEX CP™		●	●		●								1/4 inch 6 mm	1/2 inch, 2 inches with aggregate 12.7 mm to 5 cm	2 hours	N/A	22.5 sf at 1/4" 2.1 m ² at 6 mm	Versatile Concrete Repair	100% RH

The chart information represents basic product recommendations. Always refer to the ARDEX Technical Data Sheets or website prior to installation for specific product installation guidelines. ARDEX Technical Department can be reached at 888-512-7339

AF - 170 05/20
www.ardexamericas.com