

## ARDEX AMERICAS | Self-Leveling Underlayments

Product Selection Chart		Over concrete	Over ceramic tile and terrazzo	Over non-water-soluble adhesive residue	Well bonded VCT	Epoxy Coating Systems	Metal	Over wood	Over gypsum	Primer, Mechanical Prep	Pumpable	On/Above/Below Grade	Portland Cement-Based	Cement Hybrid	Can be tapered	Mix with water only	Two Component	Maximum thickness neat	With aggregate	Hours to walk on	Hours to install moisture insensitive tile & stone	Hours to install most flooring	Compressive strength (ASTM C109 Modified) at 28 days	Coverage	RH Limit
<a href="#">ARDEX K 15®</a>		●	●	●		●	●	●		Yes	●	OAB	●		●	●		1 1/2" 4 cm	5" 12 cm	2 to 3	6	16	5500 psi (386 kg/cm <sup>2</sup> )	30 ft <sup>2</sup> at 1/4" (2.79 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX K 40™ RAPID</a>		●	●	●		●				Yes	●	OAB	●		●	●		1" 2.5 cm		1 to 2	2	2	8000 psi (562 kg/cm <sup>2</sup> )	56 ft <sup>2</sup> at 1/8" (5.2 m <sup>2</sup> at 3 mm)	99% RH
<a href="#">ARDEX K 13™</a>	High Flow	●	●	●		●				Yes	●	OAB	●		●	●		1 1/2" 4 cm		2 to 3	6	16	5300 psi (371 kg/cm <sup>2</sup> )	28 ft <sup>2</sup> at 1/4" (2.6 m <sup>2</sup> at 6 mm)	99% RH
	Regular	●	●	●		●				Yes	●	OAB	●		●	●		1 1/2" 4 cm		2 to 3	6	16	5300 psi (371 kg/cm <sup>2</sup> )	26 ft <sup>2</sup> at 1/4" (2.4 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX V 1200™</a>		●	●	●		●				Yes	●	OAB	●		●	●		2" 5 cm		2 to 3	6	24	4500 psi (316 kg/cm <sup>2</sup> )	25 ft <sup>2</sup> at 1/4" (2.3 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX V 1000™</a>		●	●							Yes	●	OAB	●		●	●		1 1/4" 3 cm		4 to 5	6	24	4400 psi (309 kg/cm <sup>2</sup> )	25 ft <sup>2</sup> at 1/4" (2.3 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX K 10™</a>		●	●	●		●				Yes	●	OAB	●		●	●		1" 2.5 cm		2 to 3	6	24	4700 psi (329 kg/cm <sup>2</sup> )	50 ft <sup>2</sup> at 1/8" (4.5 m <sup>2</sup> at 3 mm)	99% RH
<a href="#">ARDEX K 60™ ARDITEX</a>		●	●	●		●	●	●		No		OAB	●		●	●	●	1/2" 12 mm		2 to 3	6	24	3500 psi (246 kg/cm <sup>2</sup> )	42 ft <sup>2</sup> at 1/8" (3.9 m <sup>2</sup> at 3 mm)	100% RH
<a href="#">ARDEX LU 100™</a>		●	●	●	●	●		●		Yes	●	A		●	●	●		2" 5 cm	5" 12 cm	3	72	72	5000 psi (350 kg/cm <sup>2</sup> )	22 ft <sup>2</sup> at 1/4" (2 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX K 22 F™</a>		●	●	●	●	●		●	●	Yes	●	A		●	●	●		1 1/4" 3 cm	2" 5 cm	2 to 3	72	24*	6000 psi (420 kg/cm <sup>2</sup> )	50 ft <sup>2</sup> at 1/8" (4.5 m <sup>2</sup> at 3 mm)	99% RH
<a href="#">ARDEX K 34™</a>		●	●			●			●	Yes	●	OAB	●		●	●		3" 7.6 cm		2 to 3	24*	24*	3000 psi (211 kg/cm <sup>2</sup> )	34 ft <sup>2</sup> at 1/4" (3.15 m <sup>2</sup> at 6 mm)	99% RH