

# ARDEX B 40™

## Trench Repair Mortar

### Fast-Setting, Horizontal Concrete Repair Mortar



Portland cement-based, polymer modified, fast setting repair mortar  
Accepts foot traffic in 2 hours, vehicular traffic in 6 hours Mixes with water only

Easy to apply – formable, pourable and pumpable  
Installs from 1/2" to 9" (12.7 mm to 22.86 cm) neat

#### Installation

##### Mixing

**Ratio:** 3 quarts (+ / - 8 oz.) (2.66 to 3.0 L)  
of water per 50 lb. (22.7 kg) bag

**Coverage:** 0.4 cu. ft. per 50 lb. bag (0.0113 m<sup>3</sup> per 22.7 kg bag)  
9.6 sq. ft. per 50 lb. bag at 1/2" (12.7 mm) (0.890 m<sup>2</sup>  
per 22.7 kg bag at 12.7 mm)

##### Pot Life / Working

**Time:** 10 - 20 minutes

##### Time to

**Traffic:** Foot - 2 hours  
Full, Including Rolling Loads - 6 hours

##### Coat or

**Seal:** Approx. 6 hours

**Color:** Gray

For complete technical documentation, please see the  
Technical Data Sheet at [www.ardexamericas.com](http://www.ardexamericas.com)



ARDEX Americas  
400 Ardex Park Drive  
Aliquippa, PA 15001  
888-512-7339

[www.ardexamericas.com](http://www.ardexamericas.com)

